



Door de kwaliteiten in spraak en muziek raken we vertrouwd met de hogere waarden van het leven. Geluid kan een vorm van kunst zijn, zoals muziek, waar velen van genieten, maar spraak heeft deze specifieke waarde, namelijk te informeren, begeleiden, onderwijzen of waarschuwen, zowel een groep mensen als een bepaald individu. Bij het gebruik van kwaliteit audiocomponenten is uw boodschap duidelijk hoorbaar in een bepaalde zone of in een groter gebied en met een hogere perceptie dan berichten die op grote schermen worden weergegeven. Omdat we hebben gekozen voor hoge kwaliteit, zijn we een samenwerking aangegaan met **AUDAC** omdat hun productkwaliteit de verwachtingen van de gebruikers overtreft, waardoor het geen toeval zal zijn dat we uw berichten overal duidelijk kunnen weergeven, overal waar ze moeten gehoord worden.

Dus gecombineerd met **voicegear** digitale audio-repeaters, kunnen we u de hoogste kwaliteit bieden met een grote keuze van luidsprekers, voor binnen- of weerbestendig buitengebruik, voorversterkers, versterkers, mixers, matrixen, oproepmicrofoons en Dante-netwerkoplossingen. We verwelkomen uw vragen.

Grâce aux qualités de la parole et de la musique, nous nous familiarisons avec les valeurs supérieures de la vie. Du son peut être une forme d'art, comme la musique, appréciée par beaucoup, mais la parole a cette valeur spécifique qui est d'informer, guider, enseigner ou avertir un groupe de personnes ainsi qu'une personne en particulier. En utilisant des composantes audio de qualité, votre message sera clairement entendu dans une zone particulière ou dans une zone plus large et avec une perception plus élevée que les messages affichés sur des grands écrans. Comme nous avons choisi la haute qualité, nous avons conclu un partenariat avec **AUDAC** car la qualité de leurs produits surpasse les attentes des utilisateurs, et ce sera donc pas une coïncidence, que nous nous pourrions diffuser vos messages clairement partout où ils doivent être entendus.

Ainsi combiné avec des répéteurs audio numériques **voicegear**, nous serons en mesure de vous fournir la plus haute qualité avec un choix de toutes sortes d' haut-parleurs, pour usage intérieur ou extérieur résistant aux intempéries, préamplificateurs, amplificateurs, mélangeurs, matrices, microphones et solutions de mise en réseau Dante. Nous accueillerons vos questions avec plaisir.

Through the qualities in speech and music we become familiar with the higher values of life. Sound can be a form of art, like music, enjoyed by many, but speech has this specific value which is to inform, guide, teach or warn a group of people as well as a particular individual. When using quality audio components, your message will be clearly heard in one particular zone or in a larger area and with a higher perception than messages displayed on wide screens. As we chose for high quality, we entered a partnership with **AUDAC** as their product quality exceeds users expectations making it no coincidence we will be able to broadcast your messages clearly anywhere they need to be heard.

So combined with **voicegear** digital audio repeaters, we will be able to provide you the highest quality with all kinds of speakers, for inside or weatherproof outside use, pre-amplifiers, amplifiers, mixers, matrixes, paging microphones, and Dante networking solutions. We will welcome your enquiries.

High Quality audio systems for indoor and outdoor announcements & music



WX302 2-way speaker systems exist in 3 sizes and are available in black & white

Dit 2-weg speaker systeem bestaat in 3 afmetingen en is leverbaar in wit en zwart

Cette enceinte acoustique à deux voies est livrable en 3 dimensions en noir et blanc



Wx302

- 1" Dome tweeter
- 3" Low frequency loudspeaker
- Vertical and horizontal mounting
- Terminal block connection (MK2 version)
- 100V and low impedance connection possibility
- Multi-tapping 100V line transformer

The WX302 is a powerful 2-way performance speaker suitable for a wide variety of applications, ensuring true-to-nature, high fidelity reproduction of music and speech. It is fitted with a 1" dome tweeter and a 3" low-frequency loudspeaker, capable of delivering a power of 30 Watt. It can be used in standard 8 Ohm systems but also in 100V PA systems with power taps for 20 Watt, 10 Watt and 5 Watt. The elegant shaped synthetic enclosure is available in two different colours (black and white), making it blend into any environment going from standard indoor home to special indoor design interiors. The included steel mounting bracket allows horizontal and vertical mounting as well as focusing of the speaker and an integrated advanced protection network protects the tweeter against overload.

This new series retains all its strengths but has also been upgraded in a few specific areas with installer convenience and durability in mind. The connection of the indoor loudspeakers is changed to a terminal block, which makes it easier to install and connect the WX MK2 series wall speaker, while daisy-chaining is made more convenient through additional connection terminals (4-pin).. Both indoor and outdoor versions are now equipped with an elegant rotatable AUDAC logo.

An outdoor weatherproof system on a pole is available only in black

Een outdoor waterproof systeem is leverbaar op paal in het zwart

Une version pour usage extérieur tout temps est livrable sur pilone uniquement en noir



Architects' and Engineers' Specifications:

The loudspeaker shall be a surface-mount 2-way type, consisting of a 3" woofer and 1" tweeter which are built in an ABS enclosure with finely perforated front grill and fitted with a line transformer allowing it to be used on both low impedance (8 Ohm) and 100 Volt distributed lines. It shall be vertically and horizontally mountable using the supplied mounting bracket. It shall have an RMS power handling of 30 Watt with a maximum power handling of 60 Watt and the frequency response (± 3 dB) shall range from 90 Hz to 18 kHz. The sensitivity shall be 85 dB when measured with an input signal of 1 Watt at a distance of 1 meter, while the maximum continuous sound pressure level shall be 100 dB. The loudspeaker shall have an impedance of 8 Ohm, a 100V line transformer and a passive built-in crossover network with a crossover frequency of 2.5 kHz. The transformer shall have multiple tapings for 20 Watt, 10 Watt and 5 Watt which are selectable, including the 8 Ohm bypass, using a rotary switch on the rear of the enclosure. The loudspeaker enclosure shall be 129 mm high, 199 mm wide and 120 mm deep and the weight shall not exceed 1.66 Kg.